


AN-MST: Straight Thread Connector



* Working Pressures

Part Number	Tube O.D.	P Thread	P1 Male SAE Thread	A	E	E1	S	L	H	Stainless Steel*	Brass*
T2AN2MST	1/8	5/16-24	5/16	1.06	.06	.06	.45	.30	7/16	6000	---
T3AN3MST	3/16	3/8-24	5/16	1.10	.13	.13	.48	.30	1/2	6000	---
T4AN4MST	1/4	7/16-20	7/16	1.23	.17	.17	.55	.36	9/16	6000	---
T4AN5MST	1/4	7/16-20	1/2	1.23	.17	.23	.55	.36	5/8	6000	---
T4AN6MST	1/4	7/16-20	9/16	1.29	.17	.30	.55	.39	11/16	6000	---
T4AN8MST	1/4	7/16-20	3/4	1.37	.17	.39	.55	.44	7/8	6000	---
T5AN5MST	5/6	1/2-20	1/2	1.23	.23	.23	.55	.36	5/8	6000	---
T6AN6MST	3/8	9/16-18	9/16	1.30	.30	.30	.56	.36	11/16	6000	---
T6AN4MST	3/8	9/16-18	7/16	1.29	.30	.17	.56	.36	5/8	6000	---
T6AN8MST	3/8	9/16-18	3/4	1.38	.30	.39	.56	.44	7/8	6000	---
T6AN10MST	3/8	9/16-18	7/8	1.50	.30	.48	.56	.50	1	6000	---
T8AN8MST	1/2	3/4-16	3/4	1.48	.39	.39	.66	.44	7/8	6000	---
T8AN6MST	1/2	3/4-16	9/16	1.38	.39	.30	.66	.39	13/16	6000	---
T8AN10MST	1/2	3/4-16	7/8	1.60	.39	.78	.66	.50	1	6000	---
T8AN12MST	1/2	3/4-16	1-1/16	1.76	.39	.61	.66	.59	1-1/4	6000	---
T10AN8MST	5/8	7/8-14	3/4	1.60	.48	.39	.76	.44	15/16	6000	---
T10AN10MST	5/8	7/8-14	7/8	1.70	.48	.48	.76	.50	1-1/4	6000	---
T10AN12MST	5/8	7/8-14	1-1/16	1.86	.48	.61	.76	.56	1-1/4	6000	---
T12AN8MST	3/4	1-1/16 - 12	3/4	1.76	.61	.39	.86	.44	1-1/8	6000	---
T12AN10MST	3/4	1-1/16 - 12	7/8	1.86	.61	.48	.86	.50	1-1/8	6000	---
T12AN12MST	3/4	1-1/16 - 12	1-1/16	1.97	.61	.61	.86	.56	1-1/4	6000	---
T12AN14MST	3/4	1-1/16 - 12	1-3/16	1.96	.61	.61	.86	.59	1-3/8	5400	---
T12AN16MST	3/4	1-1/16 - 12	1-5/16	1.99	.61	.84	.86	.59	1-1/2	5400	---
T16AN16MST	1	1-5/16 - 12	1-5/16	2.04	.84	.84	.91	.59	1-1/2	5400	---
T16AN12MST	1	1-5/16 - 12	1-1/16	1.99	.84	.61	.91	.59	1-3/8	5400	---
T20AN20MST	1-1/4	1-5/8 - 12	1-5/8	2.17	1.08	1.08	.96	.59	1-7/8	3600	---
T24AN24MST	1-1/2	1-7/8 - 12	1-7/8	2.37	1.31	1.31	1.00	.59	2-1/8	2400	---
T32AN32MST	2	2-1/2 - 12	2-1/2	2.78	1.78	1.78	1.03	.59	2-3/4	1800	---

Finger-tight assembly dimensions (shown in inches) are for reference only and subject to change. When ordering, specify material designator with part number. Click on the "How To Order" button above for complete ordering information.