


# Unilok<sup>®</sup>

## Tube To Tube Adapter

### U-ANF: Female An Adapter

Connects fractional tube to male AN

CAD Drawing Download: [go](#)



\* Working Pressures

Part Number	T Tube O.D.	AN Tube Flare Size	B	F	G Hex Flat	Gx Hex Flat	N	R	Stainless Steel*	Brass*
U2ANF2	1/8	1/8	0.73	0.53	7/16	3/8	0.54	5/16-24 UNJF-3	---	---
U2ANF4	1/8	1/4	0.75	0.53	7/16	9/16	0.62	7/16-20 UNJF-3	---	---
U4ANF4	1/4	1/4	0.84	0.62	9/16	9/16	0.62	7/16-20 UNJF-3	---	---
U6ANF6	3/8	3/8	0.98	0.39	11/16	11/16	0.72	9/16-18 UNJF-3	---	---
U8ANF8	1/2	1/2	1.25	0.91	7/8	7/8	0.85	3/4-16 UNJF-3	---	---

\*Generally, Unilok tube fittings are rated to the maximum allowable working pressures of the tubing recommended for use with the fittings. However, pressure ratings of fittings with AN integral ends may be lower. Click on the "Pressure Ratings" button above or contact your Authorized Distributor for more information regarding tubing and fitting pressure ratings.

Finger-tight assembly dimensions (shown in inches) are for reference only and subject to change. When ordering, specify material designator with part number. Click on the "How To Order" button above for complete ordering information.