




## Tube Stub Connectors/Adapters

### U-RPC: Reducing Port Connector

Port Connectors are used to close connect two Unilok tube fitting ports.



CAD Drawing Download: [go](#)

\* Working Pressures

Part Number	T Tube O.D.	Tx Reducer Tube O.D.	B	E Minimum Opening	F	Fx	V	Stainless Steel*	Brass*
U2RPC1	1/8	1/16	0.68	0.02	0.34	0.08	0.24	---	---
U4RPC1	1/4	1/16	0.71	0.02	0.34	0.14	0.37	---	---
U4RPC2	1/4	1/8	0.89	0.06	0.53	0.13	0.37	---	---
U6RPC2	3/8	1/8	0.91	0.08	0.53	0.15	0.50	---	---
U6RPC4	3/8	1/4	0.98	0.15	0.62	0.13	0.50	---	---
U8RPC4	1/2	1/4	1.15	0.15	0.62	0.15	0.62	---	---
U8RPC6	1/2	3/8	1.20	0.24	0.69	0.13	0.62	---	---
U12RPC8	3/4	1/2	1.44	0.34	0.91	0.15	0.87	---	---

\*Generally, Unilok tube fittings are rated to the maximum allowable working pressures of the tubing recommended for use with the fittings. Click on the "Pressure Ratings" button above or contact your Authorized Distributor for more information regarding tubing and fitting pressure ratings.

Finger-tight assembly dimensions (shown in inches) are for reference only and subject to change. When ordering, specify material designator with part number. Click on the "How To Order" button above for complete ordering information.